SEPARATION MACHINE



ALLMAXX S





fo@af-food-technology.com

...separation on a new level

Hygienic machine design

FlexxPress-Technology

High product diversity

MADE IN GERMANY

-en-



APPLICATION EXAMPLES









FACTS

- Throughput: 500 kg/h up to 4.5 t/h (depending on product and perforated drum)
- 3 kW motor power
- Perforated drum available in the following hole diamters: 1 mm, 1.3 mm, 2 mm, 3 mm, 5 mm, 8 mm
- "TecBelt" available in the following thicknesses: 10 mm, 13 mm, 16 mm



STANDARD EQUIPMENT



Level sensor (for an optimized separation process)



Stepless speed control (for speed adjustment to different products)



FlexxPress- Technology (enables consistent product quality)



Newly developed drum geometry (up to 80% increased lifetime, product- friendly process due to increased number of holes)



Clean, hygienic machine design enables easy handling while all components are extremely robust



INFEED VARIANTS



Funnel infeed (product feeding via a conveyor unit)



Manual infeed (product infeed via a machine operator)


OPTIONS



Display variant (enables automatic pressure control and storage of various products)



Automatic lubrication pump (with targeted grease return, cartridge lasts up to 1 year)



Pusher (for optimized product intake of larger products)